

E/Z Prime 950™
MATERIAL SAFETY DATA SHEET

APPLICATION

Water-Soluble Extrusion Primer and Lamination Adhesive

PRODUCT DESCRIPTION

Clear liquid solution

Chemtec – 24 Hour Emergency Telephone Number: 1-800-424-9300
Manufacturer: 1-800-494-2520

HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

This product is a proprietary mixture that does not have any ingredients that are hazardous under current U.S. Department of Labor definitions.

HEALTH INFORMATION & FIRST AID TREATMENT

FIRST AID: -

EYE CONTACT: Flush with water

SKIN CONTACT: Wash with soap & water, may cause mild skin irritation

INHALATION: Remove to fresh air

INGESTION: Give two glasses of water. Do NOT induce vomiting. Obtain medical advice.

HEALTH HAZARDS – TOXICOLOGY:-

No chronic problems result from exposure

E/Z Prime 950™**MATERIAL SAFETY DATA SHEET**

PERSONAL PROTECTION

Use safety glasses
Plastic or rubber gloves
No respiratory protection required

FIRE AND EXPLOSION HAZARD DATA

Flash Point: N/A

Explosive Limits: Non explosive

SPILL CONTROL PROCEDURE

Flush material with water to drain or sewer

PHYSICAL & CHEMICAL PROPERTIES

Chemical Name: None (Material is a proprietary mixture)

Density: 1.003

Specific Gravity (Water = 1): 1.007

Boiling Point: 212° F/ 100° C

Evaporation Rate: Same as water

Viscosity Of Liquid: 5-15 cps

Freezing/Melting Point: Freezes at 32° F/ 0° C

pH: 10.5-11.0

Solids: 2%

E/Z Prime 950™**MATERIAL SAFETY DATA SHEET**

REACTIVITY DATA**Stability: Stable****Incompatibility: may react with oxidizing materials****Hazardous Decomposition or Byproducts: Nitrogen Oxides & Carbon Monoxide****Conditions: Protect from Freezing****TRANSPORTATION & STORAGE****Usual Shipping Containers: 55 gallon drums or 275/300 gallon totes****Storage Temperature: 40°F/10°C to 85°F/38°C****Transport Temperature: must be above freezing – fully recoverable if frozen**

The information herein is given in good faith and to the best of our knowledge. No warranty, express or implied, is made.

4/15/2008